



**WACKER  
NEUSON**  
*all it takes!*

# DT15

## Track Dumper



### Maximum application power

The DT15 is the ideal transporter on the construction site for extensive work. The large skip selection combined with the comfortable intuitive hydrostatic drive system as well as the high payload make it the perfect versatile material handler. The single-piece engine hood and the optimal arrangement of the service points also make daily maintenance much easier, saving time and effort. The low center of gravity makes it a trustworthy partner in material transport, even with a high load.

### Hydrostatic drive



Simply start and off you go: Because of the hydrostatic drive system, no frequent gear changing is needed and the operator can focus on the task. The hydraulic drive system and the working hydraulics can be operated independently of each other.

### 3-cylinder turbo diesel engine



The powerful diesel engine offers a high level of efficiency at a low weight. With the built-in turbocharger, the machine is productive in any environment including high altitudes. By optimally matching all components, provides excellent centre of gravity.



### Interchangeable skip versions

The variety of skip versions are available making the machine versatile for every construction site. They can also be easily exchanged among each other, saving time, which means they can be adapted for every construction site situation.

### Technical Information

|                                    | Units | DT15                                |
|------------------------------------|-------|-------------------------------------|
| <b>Hydraulic</b>                   |       |                                     |
| Hydraulic pump                     |       | Variable displacement and gear pump |
| Flow rate max.                     | l/min | 95                                  |
| <b>Mechanical - Output Details</b> |       |                                     |
| Gradeability SP 80 mm              |       | 27%                                 |
| Travel speed                       | km/h  | 7.5                                 |
| <b>Mechanical Details</b>          |       |                                     |
| Length                             | mm    | 2,674                               |
| Width                              | mm    | 1,102                               |
| Height                             | mm    | 2,372                               |
| Weight                             | kg    | 1,040                               |
| Payload max.                       | kg    | 1,500                               |
| Skip                               |       | Front tip skip                      |
| Skip capacity levelled             | l     | 632                                 |
| Skip capacity heaped               | l     | 760                                 |



### Small dimensions

The compact dimensions of the machine make it ideal for manoeuvring and working in confined spaces.

|                              | Units | DT15          |
|------------------------------|-------|---------------|
| Operating weight (min.-max.) | kg    | 1,345 - 1,695 |
| <b>Engine</b>                |       |               |
| Cylinder                     |       | 3             |
| Cylinder capacity            | cm3   | 898           |
| Inclined position max.       |       | 20 λ          |
| Effective power              | KW    | 15.2          |
| Nominal engine speed         | 1/min | 2,400         |
| Stroke                       | mm    | 73            |
| Bore                         | mm    | 72            |
| Motor type                   |       | Diesel engine |
| Exhaust-gas limit            |       | EU Stage V    |
| Manufacturer                 |       | Kubota        |
| Engine designation           |       | Z - 902       |
| <b>Environment Data</b>      |       |               |
| CO2 (NRSC)                   | g/km  | 1,047.4       |
| <b>Shipping and Storage</b>  |       |               |
| Shipping weight              | kg    | 1,270         |